



Specifications

03/11/2021

To
Mid City Restaurant Supply
Tom Thomas
500 Alakawa St # 118
Honolulu, HI 96817
808-845-5755
808-989-0276 (Contact)

Project
Westin Hapuna

From
RHI Solutions
Stephanie McDaniel
13809 122nd Street E
--
Puyallup, WA 98374
(425)251-0531
425-251-0531 101 (Contact)

ITEM 1 - HD RANGE, 36", 2 OPEN BURNERS, 24" GRIDDLE (1 REQ'D)

Vulcan Model V2BG24C Dimensions: 40.5(h) x 36(w) x 41.88(d)

V Series Heavy Duty Range, gas, 36", (2) 35,000 BTU open burners, (1) 24" griddle, convection oven, stainless steel front, front top ledge, sides, base, burner box & stub back, 6" adjustable legs, 162,000 BTU, CSA Flame, CSA Star, NSF

- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea Natural gas (specify elevation if over 2,000 ft.)
- 1 ea 1" NPT pressure regulator with reducer (Natural gas)
- 1 ea 1-1/4" front manifold connection
- 1 ea Front manifold: cap & cover, right
- 1 ea 115v/60/1-ph, 4.0 amp, fan motor voltage, cord & plug, standard
- 1 ea Griddle on left
- 1 ea Salamander Broiler, natural gas, 36" wide, 30,000 BTU heavy duty infrared burner, dual control, (6) grid positions, removable pan, stainless steel front, top & sides, 3/4" gas connection & pressure regulator
- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea Reinforced Riser, for standard or convection ovens (if mounting a 36" cheesemelter or either of the salamanders on a back riser above the heavy duty range, you must add this)
- 1 ea Inter-plumbing gas connection kit (requires rear gas connection on range), for connecting 36RB/36IRB to heavy duty V-Series ranges



ELECTRICAL

	VOLTS	CYCLE	PHASE	CONN	AFF	NEMA	AMPS	KW	HP	MCA	MOCF
1	115	60	1	Cord & Plug			4				

GAS

	SIZE	MBTU	KW	CONN
1		162.0		
2	1-1/4"			
3	3/4"	30.0		

STEAM

	INLET SIZE	RETURN SIZE	LB/HR	PSIG (MIN)	PSIG (MAX)
1					
2					
3					

ITEM 2 - HD RANGE, 36", 6 OPEN BURNERS (1 REQ'D)

Vulcan Model V6B36C Dimensions: 36(h) x 36(w) x 36.75(d)

V Series Heavy Duty Range, gas, 36", (6) 35,000 BTU open burners, cast iron grates, convection oven, stainless steel front, front top ledge, sides, base, burner box & stub back, 6" adjustable legs, 242,000 BTU, CSA, NSF

- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea Natural gas (specify elevation if over 2,000 ft.)
- 1 ea 1-1/4" NPT pressure regulator (Natural gas)



- 1 ea 1-1/4" front manifold connection
- 1 ea Front manifold: cap & cover, left
- 1 ea 115v/60/1-ph, 4.0 amp, fan motor voltage, cord & plug, standard
- 1 ea Salamander Broiler, natural gas, 36" wide, 30,000 BTU heavy duty infrared burner, dual control, (6) grid positions, removable pan, stainless steel front, top & sides, 3/4" gas connection & pressure regulator
- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea Reinforced Riser, for standard or convection ovens (if mounting a 36" cheesemelter or either of the salamanders on a back riser above the heavy duty range, you must add this)
- 1 ea Inter-plumbing gas connection kit (requires rear gas connection on range), for connecting 36RB/36IRB to heavy duty V-Series ranges
- 1 ea Front Top Ledge, 48" overlapping & welded

ELECTRICAL

	VOLTS	CYCLE	PHASE	CONN	AFF	NEMA	AMPS	KW	HP	MCA	MOCP
1	115	60	1	Cord & Plug			4				

GAS

	SIZE	MBTU	KW	CONN
1		242.0		
2	1-1/4"			
3	3/4"	30.0		

STEAM

	INLET SIZE	RETURN SIZE	LB/HR	PSIG (MIN)	PSIG (MAX)
1					
2					
3					

ITEM 2.1 - HD RANGE, 12", 2 OPEN BURNERS (1 REQ'D)**Vulcan Model V2B12B Dimensions: 36(h) x 12(w) x 36.75(d)**

V Series Heavy Duty Range, gas, 12", (2) 35,000 BTU open burners, cast iron grates, storage base with cabinet doors, stainless steel front, front top ledge, sides, base, burner box & stub back, 6" adjustable legs, 70,000 BTU, CSA, NSF



- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea NOTE: Rear gas connection not available on this model. Unit must be gassed from the front & manifolded with another unit for rear gas connection.
- 1 ea Natural gas (specify elevation if over 2,000 ft.)
- 1 ea NOTE: A regulator must be used on this equipment
- 1 ea 1-1/4" front manifold connection, standard
- 1 ea Front manifold location to be specified
- 1 ea Single-deck hi-shelf riser, non-overlapping, 12"

GAS

	SIZE	MBTU	KW	CONN
1		70		
2	1-1/4"			

STEAM

	INLET SIZE	RETURN SIZE	LB/HR	PSIG (MIN)	PSIG (MAX)
1					
2					