



Submittal Sheet

09/15/2020

ITEM# 81 - HD RANGE, 24", 4 OPEN BURNERS (1 EA REQ'D)

Vulcan V4B24B

V Series Heavy Duty Range, gas, 24", (4) 35,000 BTU open burners, cast iron grates, storage base, cabinet doors, stainless steel front, front top ledge, sides, base, burner box & stub back, 140,000 BTU, 6" adjustable legs, CSA, NSF

ACCESSORIES

Mfr	Qty	Model	Spec
Vulcan	1		1 year limited parts & labor warranty, standard
Vulcan	1		Natural gas (specify elevation if over 2,000 ft.)
Vulcan	1		Front manifold: cap and cover, left ***Left section***
Vulcan	1	V4B24B	V Series Heavy Duty Range, gas, 24", (4) 35,000 BTU open burners, cast iron grates, storage base, cabinet doors, stainless steel front, front top ledge, sides, base, burner box & stub back, 140,000 BTU, 6" adjustable legs, CSA, NSF
Vulcan	1		1 year limited parts & labor warranty, standard
Vulcan	1		Natural Gas
Vulcan	1		1-1/4" front manifold connection
Vulcan	1		Front manifold: cap and cover, open ***Middle section***
Vulcan	1	VGMT36B	V Series Heavy Duty Range, gas, 36", griddle, 3/4" thick polished steel plate, snap action thermostatic controls, cabinet base, stainless steel front, top front ledge, sides, base, burner box & stub back, 6" adjustable legs, 90,000 BTU, CSA Flame, CSA Star, NSF
Vulcan	1		1 year limited parts & labor warranty, standard
Vulcan	1		Natural Gas
Vulcan	1		Single rear 1-1/4" front manifold connection on right
Vulcan	1		Front manifold: cap and cover, right
Vulcan	1		36" rapid recovery composite plate griddle, in lieu of 36" thermostatic griddle
Vulcan	1	FRTTOP-84WLD	Front Top Ledge, 84" overlapping & welded
Vulcan	1	VOVER-84	Stub Riser, 4", overlapping, for 84" ranges
Vulcan	2	GSTRIP BODY	Oven banking strip
Vulcan	1	VDOLLY 84	Dolly Frame, 84" (includes casters)
Dormont	1	16125KIT2S36	Dormont Blue Hose™ Moveable Gas Connector Kit, 1-1/4" inside dia., 36" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (2) Swivel MAX®, (1) full port valve, coiled restraining cable

Dormont

1 PS

with hardware, 461,000 BTU/hr minimum, limited lifetime warranty

(PS) Dormont Safety-Set, equipment placement system for all caster-mounted equipment, allows precise, consistent equipment placement under the fire suppression and ventilation systems, satisfies NFPA codes 17A (5.6.4) and 96 (12.1.2.3), includes two (2) units and hardware pack

See shop drawings for details

Right end

GAS

	SIZE	MBTU	KW
1		140	
2		140	
3	1-1/4"		
4		90.0	
5	1-1/4"		

STEAM

	INLET SIZE	RETURN SIZE	LB/HR	PSIG (min)	PSIG (max)
1					
2					
3					
4					
5					

7
OK 3.1

79

80

81

New
Cooking

83

84

87



