







* 84"		
12"	36" 36" ] 8 1 9 7	
<u> </u>		107 1 EA VWT12B SPREADER
		Ø MBTU 1.25 MANIFOLD
GAS[	GAS GAS ₹	8 1 EA V4B36B RANGE  140 MBTU 1.25 32 AFF  9 1 EA VCBB36C CHAR BROILER  131 MBTU 1.25 MANIFOLD
כאכ ו	C&C	GAS CONNECTION #: 1 LOCATED IN ITEM: 1 PIPE SIZE: 1.25 NPT CP HEIGHT: 32* AFF TOTAL GAS LOAD: 271 MBTU FEEDS: 9 8 7 NOTE:

## GENERAL NOTES - PLEASE READ

VENTILATION: ALL COOKING EQUIPMENT MUST BE VENTILATED BY AN APPROVED APPLIANCE IN ACCORDANCE WITH ALL APPLICABLE CODES.

FIRE SUPPRIESSION: ALL COOKING EQUIPMENT MUST BE PROTECTED BY AN APPROVED FIRE SUPPRESSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.

CONNECTIONS: ALL PIPING, FITTINGS, AND INTERCONNECTION SERVICES SHOWN ARE TO BE SUPPLIED AND INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES.

GAS CONNECTIONS:
EXTERNAL GAS REGULATORS, FLEXIBLE GAS LINES AND RESTRAINING CABLES PROVIDED WITH THE EQUIPMENT MUST BE INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES. INCOMING GAS MANIFOLD SUPPLY PRESSURE MUST NOT EXCEED 0.5 PSI (14" W.C.)

BY OTHERS: VERIFY ALL EQUIPMENT LISTED AS BY OTHERS FOR SIZE AND MECHANICAL SERVICE REQUIREMENTS.

NOTE: IN LINE WITH THE POLICY TO CONTINUALLY IMPROVE ITS PRODUCTS, THE MANUFACTURES RESERVE THE RIGHT TO CHANGE MATERIALS AND SPECIFICATIONS WITHOUT NOTICE.

06-03-2022

#	CONNECTION	POINT
(c)	COLD WATER	
(H)	HOT WATER	

HRC HOT + COLD D DRAIN POWER

\$\ SWITCH CORD SET ©≠ CONV OUTLET RECP DUPLEX RECPTACLE SINGLE RECPTACLE

(SS) STEAM SUPPLY CR STEAM RETURN

ST STEAM TAKE OFF VE EXHAUST VENT VS SUPPLY VENT RF REFRIGERATION

PROJECT CODE

**AUTH3** 

DATE: <u>06-03-202</u>2 DRAWN BY: DDB VH-AUTH3

913 WEST S ANNAPOLIS,

DESIGN