

Quote

| W V I OOD LOOFTILINI ONOOF | | | | | | | 04/27/2021 |
|------------------------------|------|--|---|-----------|-----------------------------|--------------|------------|
| Project: | | | То: | | From: | | |
| Distillery Labs Test Kitchen | | | Johnson Mechanical Service | e - Pekin | TW Food Eq | uipment Gro | up |
| | | | John Gleason | | Rich Hanson | | |
| | | | 1820 Riverway Dr. | | 701 S Ridge / | Ave | |
| | | | Pekin, IL 61554 | | Ггоу <i>,</i> ОН 453 | 74 | |
| | | | (309) 346-3434 | | 937-332-300 | 0 | |
| | | | (309)346-3434 (Contact) | | (847)975-39: | 12 (Contact) | |
| Item | Qty | С | Description | List Eac | h Discount | Net Each | Net Total |
| 1 | 1 ea | Range, 72", 4 Burne | rs, 24" Griddle, 24" Charbroile | 24,464.0 | 0 50/5/5/5 /5/5 | • | 8,991.64 |
| 99 9977 | | Packed: 1 ea) Endurance™ Restaut thermostatic griddle burners with lift-off charbroiler, 4" wide standard oven base backriser & high she | rant Range, gas, 72", (1) 24" e, 7/8" thick, (4) 30,000 BTU burner heads, (1) 24" front grease trough, (2) es, stainless steel front, sides, elf, fully MIG welded frame, 6" ,000 BTU, CSA Flame, CSA Star, | | | | |

| | Total for item 1 | | | | 12,718.15 |
|-------|--|-------------|------------------|------------|-----------|
| 2 st; | CASTERS RR4 Casters, 5" (set of 4) (2 with locks) (quantity of 2 required) | 792.00 50 | /5/5/5/5 /5/5 | 291.10 | 582.20 |
| | kit (requires rear gas connection on range), for connecting 36RB/36IRB to Endurance or Challenger Series ranges | | /5/5 | | |
| 1 ea | CONNECT-CHALL Inter-plumbing gas connection | 886.00 50 | /5/5/5/5 | 325.65 | 325.65 |
| теа | RSHELF-XL72 Reinforced highshelf, for 72" medium duty ranges (shipped in separate carton) | 1,286.00 50 | /5/5/5 /5/5 | 472.66 | 472.66 |
| | Range mount to Left Side | 0.00 | /= /= /= /= | 0.00 | 0.00 |
| 1 00 | 50,000 BTU heavy duty burner, dual control, (6) grid positions, removable pan, stainless steel front, top & sides, 3/4" gas connection & pressure regulator | 0.00 | | 0.00 | 0.00 |
| 1 ea; | | 6,594.00 | =NET= | 2,346.00 | 2,346.00 |
| 1 ea | Griddle only available on left side | 0.00 | | 0.00 | 0.00 |
| 1 ea | Natural gas (specify elevation if over 2,000 ft.) | 0.00 | | 0.00 | 0.00 |
| 1 ea | Representative for more details 1 year limited parts & labor warranty, standard | 0.00 | | 0.00 | 0.00 |
| 1 ea | NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan | 0.00 | | 0.00 | 0.00 |
| | burners with lift-off burner heads, (1) 24" charbroiler, 4" wide front grease trough, (2) standard oven bases, stainless steel front, sides, backriser & high shelf, fully MIG welded frame, 6" adjustable legs, 294,000 BTU, CSA Flame, CSA Star, NSF | | | | |
| 9.000 | Packed: 1 ea) Endurance™ Restaurant Range, gas, 72", (1) 24" thermostatic griddle, 7/8" thick, (4) 30,000 BTU | | | | |

04/27/2021

| | | • • | • | - 1, - 1, - 1 | | |
|----------|-----|--|------------|--------------------|----------|-----------|
| Item Qty | / | Description | List Each | Discount | Net Each | Net Total |
| 2 1 ea | | Work Table, Stainless Steel Top Advance Tabco FTS-3018-X (33.0 lbs total. Class: 125. Cube: 3.0. Packed: 1 ea) Special Value Equipment Filler Table, 18"W x 30"D, 18 gauge 430 stainless steel, stainless steel undershelf & legs, adjustable plastic bullet feet, NSF (filler table needs to be placed between (2) other tables for stability) | 1,339.00 | =NET= | 209.00 | 209.00 |
| 3 1 | ea | Convection Oven, Gas Vulcan VC5GD (389.0 lbs total. Class: 85. Packed: 1 ea) Convection Oven, gas, single-deck, standard depth, solid state controls, electronic spark igniter, 5-hour timer with digital display enhancement, 150° to 500°F temperature range, (5) oven racks per deck, independently operated removable door with window, porcelain on steel interior, interior light, stainless steel front, top, & sides, 23-3/4" painted legs, 1/2 HP blower motor, 50,000 BTU, NSF, NSF, CSA Star, CSA Flame, ENERGY STAR® | 12,402.00 | =NET= | 3,370.00 | 3,370.00 |
| 1 | ea | NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan Representative for more details | 0.00 | | 0.00 | 0.00 |
| 1 | ea | 1 year limited parts & labor warranty, standard | 0.00 | | 0.00 | 0.00 |
| 1 | ea | Natural gas (specify elevation if over 2,000 ft.) | 0.00 | | 0.00 | 0.00 |
| 1 | ea | 120v/60/1-ph, 7.7 amps, cord with plug, standard | 0.00 | | 0.00 | 0.00 |
| 1 | ea | VC5-OPNSTND-LG-SS Stainless steel leg stand with stainless steel shelf & adjustable rack supports on 8" stainless steel legs, for single deck oven | 2,346.00 5 | 50/5/5/5/5 /5/5 | 862.26 | 862.26 |
| 1 | st; | CSTSET-SINGLE Casters (set of four, 2 locking) for Single Deck Oven or for Leg Stand | 960.00 | =NET= | 75.00 | 75.00 |
| 1 | ea | Note: Casters will be shipped in a separate box | 0.00 | | 0.00 | 0.00 |
| | | Total for item 3 | | | | 4,307.26 |

| /5/5 ulcan MINI-JET (199.0 lbs total. Packed: 1 ea) 2MF061E-86) Mini-Jet Combi Oven Steamer V2, ectric, boilerless, left-hinged door, (4) 12"x 20"x 5", (6) 13"x18"x1", or (6) 12"x 20"x 1" pan pacity, twin control touch & knob, LCD display, 3C, JET & AUTO controls interface, customizable | | | | | | |
|--|-------------|--|--------------|----------|----------|-----------|
| /5/5 ulcan MINI-JET (199.0 lbs total. Packed: 1 ea) 2MF061E-86) Mini-Jet Combi Oven Steamer V2, ectric, boilerless, left-hinged door, (4) 12"x 20"x 5", (6) 13"x18"x1", or (6) 12"x 20"x 1" pan pacity, twin control touch & knob, LCD display, 3C, JET & AUTO controls interface, customizable | Item Qty | Description | List Each | Discount | Net Each | Net Total |
| 2MF061E-86) Mini-Jet Combi Oven Steamer V2, ectric, boilerless, left-hinged door, (4) 12"x 20"x 5", (6) 13"x18"x1", or (6) 12"x 20"x 1" pan pacity, twin control touch & knob, LCD display, 3C, JET & AUTO controls interface, customizable | 1 ea | Combi Oven, Electric | 18,558.00 50 | | 6,820.92 | 6,820.92 |
| eaning, auto-reversing fan, LED light strip, cool uch door, USB & food probe ports, drain water mpering, 4" legs, ventless capable, 208v/60/3- n, cord, NEMA L15-30P, NSF, cULus (Field onvertible to 208v/60/1-ph, 240v/60/1-ph or | | Vulcan MINI-JET (199.0 lbs total. Packed: 1 ea) (V2MF061E-86) Mini-Jet Combi Oven Steamer V2, electric, boilerless, left-hinged door, (4) 12"x 20"x 2.5", (6) 13"x18"x1", or (6) 12"x 20"x 1" pan capacity, twin control touch & knob, LCD display, ABC, JET & AUTO controls interface, customizable recipes & factory pre-programed, automatic cleaning, auto-reversing fan, LED light strip, cool touch door, USB & food probe ports, drain water tempering, 4" legs, ventless capable, 208v/60/3-ph, cord, NEMA L15-30P, NSF, cULus (Field convertible to 208v/60/1-ph, 240v/60/1-ph or 240v/60/3-ph) | | | | |
| eck out after the unit has been fully installed & ut into service. contact your Vulcan | 1 ea | NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan Representative for more details | 0.00 | | 0.00 | 0.00 |
| year limited parts & labor warranty, standard 0.00 0.00 0.00 | 1 ea | 1 year limited parts & labor warranty, standard | 0.00 | | 0.00 | 0.00 |
| ljustable feet with floor flange brackets, /5/5 | 1 ea | MINI-STAND Equipment Stand, (2) shelves, adjustable feet with floor flange brackets, stainless steel, for Mini-Jet | 1,648.00 50 | | 605.72 | 605.72 |
| | 1 ea | Filtration System | 0.00 | | 0.00 | 0.00 |
| OTE: Water is a customer supplied utility just O.00 O.00 O.00 O.00 O.00 O.00 O.00 O.0 | | NOTE: Water is a customer supplied utility just like Gas & Electric to the equipment. Proper Water Filtration based on customer water quality is essential to meet the equipment water spec requirements. Verify type of filtration needed based on performing a cold water analysis from the customer site. A suitable Water Treatment System & regular filter replacements coupled with routine cleaning/deliming is required. | 0.00 | | 0.00 | 0.00 |
| stem, with 30,000 gallon capacity, for chlorine & /5/5 lloramine reduction, sediment, bad tastes & lors, total organic compounds, tannins & | 1 ea | CB30K-SYSTEM Single Hollow Carbon Filter System, with 30,000 gallon capacity, for chlorine & chloramine reduction, sediment, bad tastes & odors, total organic compounds, tannins & trihalomethanes, ANSI/NSF 42 & 53 | 1,816.00 50 | | 667.46 | 667.46 |
| oted out of Reverse Osmosis System 0.00 0.00 0.00 | 1 ea | Opted out of Reverse Osmosis System | 0.00 | | 0.00 | 0.00 |
| Total for item 4 8,094.10 | | Total for item 4 | | | | 8,094.10 |

| Item | Qty | Description | List Each | Discount | Net Each | Net Total |
|------|-------|---|-----------|--------------------|----------|-----------|
| 5 | 1 ea | Multi-Function Cooker, Electric | 18,506.00 | 50/5/5/5/5 /5/5 | 6,801.81 | 6,801.81 |
| | | Vulcan VCS18 (Packed: 1 ea) V-Series Multifunction Cooker, electric, 18", single tank (front-to-back), 5 gallon capacity, (6) heating elements, 450°F maximum temperature, water dispenser with integrated safety valve, (2) covers per tank, drain & detachable drain pipe, stainless steel construction, 6" adjustable legs, 9.0kW, NSF, cETLus | | 7373 | | |
| | 1 ea | • | 0.00 | | 0.00 | 0.00 |
| | | 208v/60/3-ph, 25.0 amps, standard | 0.00 | | 0.00 | 0.00 |
| | 1 ea; | STRCH-SKIMMER Starch Skimmer Drain Plug, for use as a pasta cooker | 938.00 5 | 50/5/5/5 5/5/ | 344.76 | 344.76 |
| | 1 st; | CASTERS VULSCR Set of 4 adjustable casters, 6" overall height, battery screw mount, (2) with brakes | 628.00 5 | 50/5/5/5/5 /5/5 | 230.82 | 230.82 |
| | | Total for item 5 | | | | 7,377.39 |
| 6 | 1 ea | Refrigerated Work Top Traulsen CLUC-48R-SD-WTLL (310.0 lbs total. Class: 150. Cube: 39.7. Packed: 1 ea) Centerline™ Compact Undercounter Refrigerator with Work Top, two-section, 48" W, 13.28 cu. ft. capacity, self-contained rear-mount refrigeration, (2) left hinged solid doors (field reversible), electronic control with LED display, (2) epoxy coated shelves per section, 4" backsplash, stainless steel exterior, anodized aluminum interior, (4) casters, R450A refrigerant, 1/4 HP, 115v/60/1-ph, 3.6 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation, ENERGY STAR® | 7,521.00 | 50/10/27 | 2,470.65 | 2,470.65 |
| | 1 ea | 3 year parts & labor, 5 year compressor, standard | 0.00 | | 0.00 | 0.00 |
| 7 | 1 ea | Reach-In Freezer Traulsen CLBM-23F-FS-L (350.0 lbs total. Class: 150. Cube: 73.0. Packed: 1 ea) Centerline™ Freezer, Reach-in, one-section, 19.89 cu. ft., self-contained bottom mount refrigeration, left hinged full-height solid door (field reversible), electronic control with LED display, (3) epoxy coated shelves per section, stainless steel front, anodized aluminum sides and interior, (4) casters, R448A refrigerant, 1/4 HP, 115v/60/1-ph, 6.5 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation | 10,175.00 | 50/10/27 | 3,342.49 | 3,342.49 |
| | 1 ea | | 0.00 | | 0.00 | 0.00 |
| | | | | | | _ |

| | | Trw Food Equipment Group | | | | | |
|---------|------|---|-----------|----------|-----------|-----------|--|
| Item | Qty | Description | List Each | Discount | Net Each | Net Total | |
| 10 | 1 ea | Reach-In Freezer Traulsen CLBM-49F-FS-LL (575.0 lbs total. Class: 150. Cube: 122.0. Packed: 1 ea) Centerline™ Freezer, Reach-in, two-section, 43.88 cu. ft., self-contained bottom mount refrigeration, (2) left hinged full-height solid doors (field reversible), electronic control with LED display, (3) epoxy coated shelves per section, stainless steel front, anodized aluminum sides and interior, (4) casters, R448A refrigerant, 1/2 HP, 115v/60/1-ph, 11.1 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation | 14,269.00 | 50/10/27 | 4,687.37 | 4,687.37 | |
| | 1 ea | 3 year parts & labor, 5 year compressor, standard | 0.00 | | 0.00 | 0.00 | |
| 11 1 ea | | Hobart AM16VLT-ADV-2 (Packed: 1 ea) Ventless Dishwashing Machine, tall chamber door type, energy recovery, automatic soil removal (ASR), drain water energy recovery (DWER), high temp sanitizing, 208-240v/60/3 (field convertible to single phase), internal condensing system, 40 racks/hour, straight-thru or corner installation, user-friendly smart touchscreen controls, Sense-A-Temp™ booster, electric tank heat, and X-shaped wash arms, scrap screen and basket, door actuated start, door locks, stainless steel tank, tank shelf, chamber, trim panels, frame & feet, pumped drain air gap, drain water tempering, cULus, NSF, ENERGY STAR®. Factory Startup - Free for installations within 100 miles of a Hobart Service Office during normal business hours with appropriate notice; installation beyond 100 miles will be quoted by Service. | 30,270.00 | 30/10 | 19,070.10 | 19,070.10 | |
| | | Standard warranty - 1-Year parts, labor & travel time during normal working hours within the USA | 0.00 | | 0.00 | 0.00 | |
| | 1 ea | CORNER-INST-AM16 Splash Shield for Corner Installations – Includes splash panel and sheet pan adaptor | 418.00 | 30/10 | 263.34 | 263.34 | |
| | | Total for item 11 | | | | 19,333.44 | |

| | | | • | | | , , | |
|------|------|---|-----------|----------|----------|-----------|--|
| Item | Qty | Description | List Each | Discount | Net Each | Net Total | |
| 13 | 1 ea | Reach-In Refrigerator Traulsen CLBM-49R-HS-LL (575.0 lbs total. Class: 150. Cube: 122.0. Packed: 1 ea) Centerline™ Refrigerator, Reach-in, two-section, 43.88 cu. ft., self-contained bottom mount refrigeration, (4) left hinged half-height solid doors (field reversible), electronic control with LED display, (3) epoxy coated shelves per section, stainless steel front, anodized aluminum sides and interior, (4) casters, R450A refrigerant, 1/2 HP, 115v/60/1-ph, 6.7 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation | 11,356.00 | 50/10/27 | 3,730.45 | 3,730.45 | |
| | 1 ea | 3 year parts & labor, 5 year compressor, standard | 0.00 | | 0.00 | 0.00 | |
| 14 | | Heated Holding Proofing Cabinet, Mobile Vulcan VP18 (236.0 lbs total. Class: 100. Packed: 1 ea) Proofing Heated Cabinet, mobile, non-insulated, (18) 18" x 26" x 1" sheet pans or (36) 12" x 20" x 2-1/2" steam table pans, fan & air tunnel, includes (10) pair of adjustable tray slides 3" OC, 1/2 gallon water pan, switch can be set to proof or set for heated holding up to 190° F, glass door, stainless steel construction, includes drip trough & removable drip pan, 5" casters; 2 swivel, 2 rigid with locks, 120v/50/60/1-ph, 2.0kW, cord with NEMA 5-20P, cULus, UL EPH | 6,364.00 | =NET= | 1,960.00 | 1,960.00 | |
| | 1 ea | 1 year limited parts & labor warranty, standard | 0.00 | | 0.00 | 0.00 | |
| | 1 ea | 10 year warranty on heating elements, standard | 0.00 | | 0.00 | 0.00 | |
| 15 | 1 ea | Undercounter Refrigerator Traulsen CLUC-48R-GD-LR (310.0 lbs total. Class: 150. Cube: 39.7. Packed: 1 ea) Centerline™ Compact Undercounter Refrigerator, Reach-in, two-section, 48" W, 13.28 cu. ft. capacity, self-contained rear-mount refrigeration, (1) left hinged/ (1) right hinged glass doors (field reversible), electronic control with LED display, (2) epoxy coated shelves per section, stainless steel exterior, anodized aluminum interior, (4) casters, R450A refrigerant, 1/4 HP, 115v/60/1-ph, 3.6 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation, ENERGY STAR® | 8,827.00 | 50/10/27 | 2,899.67 | 2,899.67 | |
| | 1 ea | | 0.00 | | 0.00 | 0.00 | |

| Item | Qty | | Des | cription | | List Each | Discount | Net Each | Net Total |
|--|------------|--|---|---|--|------------|---------------------------------------|----------|-----------|
| 16 | 1 ea | Traulsen CLUC-48R-GD-LR (310.0 lbs total. Class: 150. Cube: 39.7. Packed: 1 ea) Centerline™ Compact Undercounter Refrigerator, Reach-in, two-section, 48" W, 13.28 cu. ft. capacity, self-contained rear-mount refrigeration, (1) left hinged/ (1) right hinged glass doors (field reversible), electronic control with LED display, (2) epoxy coated shelves per section, stainless steel exterior, anodized aluminum interior, (4) casters, R450A refrigerant, 1/4 HP, 115v/60/1-ph, 3.6 amps, NEMA 5-15P plug, cETLus, ETL-Sanitation, ENERGY STAR® | | | | | 50/10/27 | 2,899.67 | 2,899.67 |
| | | | | year compr | essor, standard | 0.00 | | 0.00 | 0.00 |
| 17 1 ea Planetary Mixer Hobart HL200-1STD 100-120/50/60/1; E beater, whip & spir configuration - Lega quart, (3) fixed spe transmission, 15-m hub, manual bowl aluminum "B" beat whip, aluminum "E steel bowl guard, 1 | | | HL200-1STD (28 0/50/60/1; Ben whip & spiral or ration - Legacy 3) fixed speeds ission, 15-minu anual bowl lift, um "B" beater, luminum "ED" | ch type mix dough arm, Planetary N s plus stir sp te SmartTin stainless st stainless st spiral dougl np, cord wit | er; with bowl, US/EXP Aixer, Bench, 20 beed, gear-drive her™, #12 taper teel bowl, eel "D" wire h arm, stainless th plug | | | 5,005.98 | 5,005.98 |
| | | | _ | _ | s within the USA | | | | |
| | 1 ea; | the top HL200 r attachn | shelf is drilled nixer, includes | for mountir 4 posts for shelf for ad | • | | 30/10 | 1,831.41 | 1,831.41 |
| | | | | Total for | item 17 | | | | 6,837.39 |
| | | | | | Merchandise | • | | | 80,867.03 |
| | | | | | Grand Total | - | | | 80,867.03 |
| N 1fr | FO- |) | 710 | | Ifacturer Sumr | - | Tatal | Torms | Notes |
| Mfr | FOE | • | ZIP | Class | Weight 0 | Good Until | Total | Terms | Notes |
| Advance Tabco Hobart | Kau Tro | fman | 75142-0000 45373-3000 | 125 | 33 280 | | \$209.00 \$26,170.83 | | |
| Traulsen | | • | 76106-1928 | 150 | 2,430 | | \$20,170.83 | | |
| Vulcan | | | 40201 | 85 | 633 | | \$17,256.23 | | |
| Vulcan | | isville | 40201 | 55 | 199 | | \$15,240.67 | | |
| Vulcan | | isville | 40201 | 100 | 236 | | \$1,960.00 | | |
| | | | | | | | · · · · · · · · · · · · · · · · · · · | | |