





151	1 E	E AI	6IRB	SAL	AMAN	DER			
()	30 1	MBTU	0.75		MANI	FOLD	INTERPLUMB		
148	148 1 EA V2FT36				RANGE				
(1)	5Ø 1	MBTU	1.25		MANI	FOLD			
149	149 1 EA VSC72 R				REFRIGERATED BASE				
③	16	20(1) Б.7А		5-15				
152	1 E	IA V	'6B36	RAN	GE				
	210 1	MBTU	1.25		32 A	FF	_		
CAC	CONNI	ECTIO	N #• 1						
GAS CONNECTION #: 1 LOCATED IN ITEM: 148									
PIPE SIZE: 1.25 NPT									
CP HEIGHT: 32° AFF									
TOTAL GAS LOAD: 290 MBTU FEEDS: 140 148 151									
	.DJ. 1	TE 17	O IJI						





GENERAL NOTES - PLEASE READ

VENTILATION: ALL COOKING EQUIPMENT MUST BE VENTILATED BY AN APPROVED APPLIANCE IN ACCORDANCE WITH ALL APPLICABLE CODES.

FIRE SUPPRIESSION: ALL COOKING EQUIPMENT MUST BE PROTECTED BY AN APPROVED FIRE SUPPRESSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.

CONNECTIONS:
ALL PIPING, FITTINGS, AND INTERCONNECTION SERVICES SHOWN ARE TO BE SUPPLIED
AND INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES.

GAS CONNECTIONS:
EXTERNAL GAS REGULATORS, FLEXIBLE GAS LINES AND RESTRAINING CABLES PROVIDED WITH THE EQUIPMENT MUST BE INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES. INCOMING GAS MANIFOLD SUPPLY PRESSURE MUST NOT EXCEED 0.5 PSI (14" W.C.)

BY OTHERS: VERIFY ALL EQUIPMENT LISTED AS BY OTHERS FOR SIZE AND MECHANICAL SERVICE REQUIREMENTS.

NOTE: IN LINE WITH THE POLICY TO CONTINUALLY IMPROVE ITS PRODUCTS, THE MANUFACTURES RESERVE THE RIGHT TO CHANGE MATERIALS AND SPECIFICATIONS WITHOUT NOTICE.

06-18-2022

4	CONNECTION	POI
\bigcirc	COLD WATER	

(C) COLD WATER

(H) HOT WATER

(HC) HOT + COLD
WATER

D DRAIN

POWER

SWITCH

CORD SET

C = CONV OUTLET RECP

DUPLEX RECPTACLE

SINGLE RECPTACLE

SINGLE RECPTANT
GAS
(SS) STEAM SUPPLY
CR STEAM RETURN

CR STEAM RETURN
ST STEAM TAKE OFF
VE EXHAUST VENT
VS SUPPLY VENT
RF REFRIGERATION

PROJECT CODE

MAVR2

THE VULCAN HART COMPANY BALTIMORE, MARYLAND

DATE: 06/17/2022

DRAWN BY: DDB

VH-BAVR1

reet 21401

913 A West St Annapolis, MD 410-263-1200

OF _