





17 1 EA 72-55-6B-36G RANGE





GENERAL NOTES - PLEASE READ

VENTILATION: ALL COOKING EQUIPMENT MUST BE VENTILATED BY AN APPROVED APPLIANCE IN ACCORDANCE WITH ALL APPLICABLE CODES.

FIRE SUPPRIESSION: ALL COOKING EQUIPMENT MUST BE PROTECTED BY AN APPROVED FIRE SUPPRESSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.

CONNECTIONS: ALL PIPING, FITTINGS, AND INTERCONNECTION SERVICES SHOWN ARE TO BE SUPPLIED AND INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES.

GAS CONNECTIONS:
EXTERNAL GAS REGULATORS, FLEXIBLE GAS LINES AND RESTRAINING CABLES PROVIDED
WITH THE EQUIPMENT MUST BE INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE
WITH ALL LOCAL CODES. INCOMING GAS MANIFOLD SUPPLY PRESSURE MUST
NOT EXCEED 0.5 PSI (14" W.C.)

BY OTHERS: VERIFY ALL EQUIPMENT LISTED AS BY OTHERS FOR SIZE AND MECHANICAL SERVICE REQUIREMENTS.

NOTE: IN LINE WITH THE POLICY TO CONTINUALLY IMPROVE ITS PRODUCTS, THE MANUFACTURES RESERVE THE RIGHT TO CHANGE MATERIALS AND SPECIFICATIONS WITHOUT NOTICE.

09-29-2022

onnection PC 💠
C COLD WATER
FILTERED WATE
H HOT WATER
HRC HOT + COLD
D DRAIN
POWER
\$ _switch
CORD BUTLET R
€ DUPLEX RECPTA
→ SINGLE RECPTA

(SS) STEAM SUPPLY

CR STEAM RETURN VE EXHAUST VENT
VS SUPPLY VENT (RF) REFRIGERATION

> PROJECT CODE ULUTH

DATE: 09/28/2022 DRAWN BY: DDB

913 A West Stannapolis, MD 410-263-1200